



C	A	Q	N	0022	F01	V01
---	---	---	---	------	-----	-----

Date : 13th September 2022

ANNEXURE - I

Rule No.	Sub Rule(s)	Compliance Verified For		Standard	
93	(1)(A), (1)(B), (2) & (3)	Motor Vehicle width, length and height		-	
94	(1), (2) & (3)	Condition of tyres		-	
95	(1), (2), (3), (4), (5), (6) & (7) (Tubeless & Radial)	Size & ply rating of tyres		IS-15633:2005, AIS-051:2004	
		Front / Rear / Spare	165/80 R14 85T		Bridgestone , Apollo & JK Tyre
		Front / Rear	185/65 R15 88T		Bridgestone, MRF & JK Tyre
			185/65 R15 88H	Apollo	
(8)	Temporary Spare Wheel	165/80R14 85T	Bridgestone , Apollo & JK Tyre	AIS-110:2009	
	(8)	Tyre pressure monitoring system		NA	
96	(1), (2), (3), (4)(ii), (4B), (7)(a) & (8)	Brakes		IS-15986:2015	
	(10)	Electronic Stability Control		AIS-133:2016	
	(11)	Brake assist System		AIS-152:2018	
96B	(a) & (b)	High Speed Brake Requirements		IS-15986:2015	
98	(3)	Steering gear		IS-11948:2010	
	(1), (2)			IS-12222:2011	
99	-	Forward and backward motion		-	
100	(1), (2), (3) & (3c)	Safety glass		IS 2553 (Part 2)(Rev.1) :2019	
101	(1) & (2)	Windscreen wiper		IS-15804:2008	
102	(1) & (2)	Signalling devices, direction indicators and stop lights		-	
103	(1) & (2)	Position of the indicator		-	
104	(1) & (4)	Fitment of reflectors		AIS-057 (Rev. 1): 2010	
105	(1) (a), (2), (3), (4) & (7)	Lamps		-	
106	(1)	Deflection of lights		-	
108	(1)	Use of red or white lights		-	
109	-	Parking light		-	
111	-	Prohibition of spotlights etc.		-	
114	(1) & (2)	Exhaust gases and exhaust pipes		-	
115	(1), (2)(i), 18(i)	Emission of smoke, vapour, etc. from motor vehicle (Bharat Stage - VI (Including OBD I))		AIS-137	
115G	(1) & (2)	Fuel Consumption Standard		AIS-137	
117	(1) & (2)	Speedometer		IS-11827:2008	
118	(1)	Speed Governor		NA	

ICAT Ref No.	2022-1285 [IOCS No: 161477]
Emission Report No.	CT0PQ 0232 dt. 15.01.2021 & CT0PR 0860 dt. 07.07.2022
Noise Report No.	CT0VP 0832 dt. 28.10.2020
FTP Report No.	TA-2020 (Bharat Stage VI) / ELTR/2018-2019/594 dt. 26.03.2019
Horn Inst. Report No.	CT0VP 0833 dt. 28.10.2020

AUTHORISED SIGNATORY	
	