



C A R N

Date : 07th December 2022

ANNEXURE - I

Rule No.	Sub Rule(s)	Compliance Verified For		Standard	
93	(1)(A), (1)(B) & (2)	Motor Vehicle Width, Length & Height		-	
94	(1), (2) & (3)	Condition of tyres		-	
95	(1), (2), (3), (4); (5) & (6) (Tubeless)	Size & ply rating of tyres		IS 15627:2005 & AIS-050:2004	
		Front	90/90-12 54J		CEAT, TVS, MRF, MAXXIS
		Rear	90/100-10 53J		
96	(1), (2), (3), (4)(ib), (4)(A), (7)(c) & (8)	Brakes with CBS		IS 14664:2010	
102	(1), (2) & (3)	Signaling devices, direction indicators and stop lights		-	
103	(1)	Position of the indicator		-	
104	(1) & (4)	Fitment of reflectors		AIS-057 (Rev. 1): 2010	
105	(1)(bb), (2)(i) & (4)	Lamps		-	
106	(1)	Deflection of lights		-	
108	(1)	Use of red or white lights		-	
111		Prohibition of spotlights etc.		-	
114	(1) & (2)	Exhaust gases and exhaust pipes		-	
115	(1), (2)(i), (19)(i)	Emission of smoke, vapour, etc. from motor vehicle (Bharat Stage - VI (Including OBD II))		AIS 137	
117	(1) & (2)	Speedometer		IS 11827:2008	
119	(1) & (2)	Installation (Below 7kW)		IS 15796:2008	
		Limit :	83 dB(A) to 112 dB(A)		
		Observed :	101.5 dB(A)		
120	(1) (2)	Performance		IS 1884:1993	
		Silencers			
		Pass by Noise	Limit : 77 dB(A) (80 < cc ≤ 175) Observed : 70.4dB(A)/71dB(A)/69.7dB(A)		
122	(1) & (2)	Embossment of chassis number & engine number & month of manufacture (Ref: Table 11 of the Technical Specifications)		AIS-065:2005	
123	(1)(a)	Safety devices in motor cycle (Pillion Hand Hold)		IS 14495:1998	
123	(2)	Safety devices in motor cycle (Footrest)		AIS 148:2018	
123	(4)	Safety devices in motor cycle (Stand)		AIS 146:2018	
123	(5)	Safety devices in motor cycle (External Projection)		AIS 147:2018	
ICAT Ref No.	2022-1115 [IOCS No. : 160205]				
Emission Report No.	CTOPR 1169 Dt: 06.12.2022				
FTP Report No.	CTOER 0359 dt. 22.09.2022				
Noise Report No.	CTOVR 1608 dt. 18.11.2022				
Horn Inst. Report No.	CTOVO 0831 dt. 22.08.2019				

AUTHORISED SIGNATORY

			
<p>VIJAYANTA AHUJA DEPUTY GENERAL MANAGER</p>		<p>SAURABH DALELA DIRECTOR</p>	<p>Page 2 of 5</p>