



C A Q N 0194 V05

**ANNEXURE - I
(Contd.)**

Date : 09th January 2023

Rule No.	Sub Rule(s)	Compliance Verified For		Standard	
119	(1) & (2)	Horns	Installation	IS-15796:2008	
			Limit :		87 dB(A) to 112 dB(A)
			Observed :		98.5 dB(A)
			Performance	IS-1884:1993	
120	(1) (2)	Pass by Noise	Silencers	-	
			Limit :	78 dB(A)	
			Observed :	74 dB(A)	
122	(1) & (2)		Embossment of chassis number & engine number & month of manufacture (Ref: Table 11 of the Technical Specifications)	AIS-065:2005	
124	Refer Annexure-IA & IB		Safety standards of components as applicable	-	
	1(A)		Rear Under Run Protective Device	IS:14812-2005	
			Vehicle Lateral Protection Side	IS: 14682-2004	
125	(6)(For M2, M3, N1, N2 & N3)		Safety Belt, Seats & their Anchorages, Head Restraints	AIS-023:2005	
	(2) (c)	Rear View Mirror	Specifications	AIS-001 (Part 1) (Rev.1):2011	
			Installation	AIS-002 (Part 1) (Rev.1):2011	
	(10)			Additional Safety features for Category M & N Vehicles	AIS-145:2017
	H(1, 2 & 3)		Intelligent transportation systems	AIS 140:2016	
138	(4) (c)		Warning Triangles- Size & Specifications	AIS-022:2001	

ANNEXURE - IA

Rule 124 (1) Table Sr. No.	Parts / Components / Assemblies	Standard	4 Wheelers (M3 Category)
1(a) & 1(c)	Automobiles lamps (bulbs)	AIS-034 (Part 1) (Rev.1)-2010	✓
2	Hydraulic brake hose (if fitted)	IS-7079:2008	NA
3	Hydraulic brake fluid (if fitted)	IS:8654-2001	NA
7(a)	Fuel Tank (Metallic)	AIS-095:2007	✓
8	Wheel Rims	IS:9438-2018	✓
11	External Projections	IS:13942-1994	✓
12	Retention and release of windows (Passenger Vehicles)	IS:13944-1994	✓
14	Wheel Nuts, Disc & Hub Caps	IS:13941-1994	✓
15	Accelerator Control System	IS:14283-1995	✓
16	Door Locks and Door Retention Components	IS:14225-1995	✓
17	Hood Latch	IS:14226-1995	NA
18	Tell Tale symbols and control	AIS 071-2009 (Part 1 & Part 2)	✓
20	Installation of Lighting/ Signalling Devices	Performance Requirements	✓
		With Vertical Orientation	✓

AUTHORISED SIGNATORY

MADHUSUDAN JOSHI DEPUTY GENERAL MANAGER	SAURABH DALELA DIRECTOR
	Page 3 of 6