



C	A	M	D	0693	F01
---	---	---	---	------	-----

Date : 17th January 2023

ANNEXURE - I

Rule No.	Sub Rule(s)	Compliance Verified For			Standard						
93	(1)(A)(X),1(B)(iv),2(d)	Motor Vehicle Width, Length and Height:			-						
94	(1), (2) & (3)	Condition of tyres			-						
95-A	(1) & (2)	Size & ply rating of tyres for agricultural tractors		Make	IS:13154-1991						
		Front	6.00-16, 8PR, (6.50-16, 8PR (Opt.)(Base, V1)	MRF/Apollo/ Good year/BKT							
		Rear	13.6-28, 12 PR & 12.4-28, 12PR(Opt.)								
96	(1), (2), (7)(d), & (8)	Brakes			-						
96-C	-	Brakes for agricultural tractor			IS:12061-1994 & IS:12207-2014						
98-B	(1), (2) & (3)	Steering Gears for agricultural tractors			IS:11859-2004 & AIS:042-2004						
99	-	Forward and backward motion			-						
101	(1) & (2)	Windscreen Wiper			NA						
102	(1) & (2)	Signaling devices, direction indicators and stop lights			-						
103	(1) & (2)	Position of the indicator			-						
104-B	(1) & (2)	Fitment of reflectors for agricultural tractors			AIS-057 (Rev. 1): 2010						
105	(1)(a), (2), (3), (4) & (7)	Lamps			-						
106	(1)	Deflection of lights			-						
108	-	Use of red or white lights			-						
109	-	Parking light			-						
111	-	Prohibition of spotlights etc.			-						
114	(1)	Exhaust gases and exhaust pipes			IS 12239 (Part 1):1996						
115 A	(2), (3) & (7)	Emission of smoke, vapour, etc. from Agricultural Tractor			-						
117	(1)	Speedometer			-						
119	(1) & (2)	Horns			IS 1884:1992						
120	(1) & (3)	Silencers	Bystander Noise		AIS:115 (Part 1& Part 2) - 2009						
			Limit (dB (A)) :	Measured (dB (A)) :							
			88	87							
			Driver Perceived Noise Level								
			Limit (dB (A)) :	Measured (dB (A)) :							
ICAT Ref No.		IOCS NO. 164158									
Emission Report No.		CORE 0683 Dt. 22.06.2022									
Noise Report No.		CT0VR-0869 Dt. 15.06.2022									
AUTHORISED SIGNATORY											
		 INTERNATIONAL CENTRE FOR AUTOMOTIVE TECHNOLOGY MANESAR									
MADHUSUDAN JOSHI DEPUTY GENERAL MANAGER			SAURABH DALELA DIRECTOR								
											
Page 2 of 4											