



C A S B 0491

Date : 03rd May 2023

ANNEXURE - I

Rule No.	Sub Rule(s)	Compliance Verified For		Standard	
93	(1)(A), (1)(B), (2)	Motor vehicle width, length and height		-	
94	(1), (2), (3)	Condition of tyres		-	
95	(1), (2),(3), (4), (5) & (6) (Tube Type)	Size & ply rating of tyres		IS 15627:2005 & AIS-050-2004	
		Front	3.75-12, 66B		CEAT
			3.75-12, 54L,		RALSON
		Rear	90/90-12, 54J		TVS
90/90-12, 66E	MRF				
96	(1), (2), (3), (4)(i), (7)(b)	Brakes		IS 14664:1999	
99	-	Forward and backward motion		-	
100	(1),(2),(3)	Safety glass		NA	
101	(1),(2)	Windscreen Wiper		NA	
102	(1), (2)	Signaling devices, direction indicators and stop lights		-	
103	(1), (2)	Position of the indicator		-	
104	(1)(v),(4)	Fitment of reflectors & reflective tapes		AIS-057(Rev.1):2010 & AIS-090-2005	
105	(1)(b), (3), (4), (5), (7)	Lamps		-	
106	(1)	Deflection of lights		-	
108	(1)	Use of red or white lights		-	
109	-	Parking lights		-	
110	-	Lamps for three wheelers		-	
111	-	Prohibition of spotlights etc.		-	
119	(1) & (2)	Horns	Installation	IS 15796:2008	
			Limit :		83 dB(A) to 112 dB(A)
			Observed :		94.3 dB (A)
			Performance	IS 1884:1993	
122	(1) & (2)	Embossment of chassis number & motor number & month of manufacture (Ref: Table 11 of the Technical Specifications)		AIS-065-2005	
124	-	Safety standards of components as applicable		Refer ANNEXURE - IA & IB	
125	(2)(a)	Rear View Mirror	Specifications	AIS-001 (Part-2)Rev.1:2011	
			Installation	AIS-002 (Part-2)Rev.1:2011	

ICAT Ref No.	2022-2111, (IQCS :165078)
Power Test Report No.	CT0PN 0664 Dt. 17.09.2018 & CT0PS 0419 Dt.14.03.2023
Horn Inst. Report No.	CT0VN 1601 Dt. 10.10.2018

AUTHORISED SIGNATORY				
MADHUSUDAN JOSHI DEPUTY GENERAL MANAGER		SAURABH DALELA DIRECTOR		
				Page 2 of 3