



C A T B 0016





Date : 05<sup>th</sup> January 2024

ANNEXURE - I

Rule No.	Sub Rule(s)	Compliance Verified For		Standard	
93	(1)(A), 1(B), 2	Motor vehicle width, length and height		-	
94	(1), (2) & (3)	Condition of tyres		-	
95	(1), (2), (3), (4), (5) & (6) (Tubeless)	Size & ply rating of tyres		IS 15627:2005 & AIS-050:2004	
		Front / Rear	Make		
		3.00-10 42J 4PR	CEAT		
		90/90-10 50J 4PR	JK Tyre		
96	(1), (2), (3), (4)(ib), (7)(c) & (8)	Brakes with CBS		IS 14664:2010	
102	(1), (2) & (3)	Signaling devices, direction indicators and stop lights		-	
103	(1)	Position of the indicator		-	
104	(1) & (4)	Fitment of reflectors		AIS-057 (Rev. 1): 2010	
105	(1)(bb), (2)(i) & (4)	Lamps		-	
106	(1)	Deflection of lights		-	
108	(1)	Use of red or white lights		-	
111	-	Prohibition of spotlights etc.		-	
117	(1) & (2)	Speedometer		IS 11827:2008	
119	(1) & (2)	Installation (Below 7kW)		IS 15796:2008	
		Limit :	83 dB(A) to 112 dB(A)		
		Observed :	83.6 dB(A)		
		Performance			IS 1884:1993
120	(2)	Pass by Noise	Limit :	75 dB(A)	IS 3028:1998
			Observed :	61 dB(A)	
122	(1) & (2)	Embossment of chassis number & motor number & month of manufacture (Ref: Table 11 of the Technical Specifications)		AIS-065:2005	
123	(1)	Safety devices in motor cycle	Pillion Handhold		IS 14495:1998
	(2)		Footrests		AIS 148:2018
	(4)		Stand		AIS 146:2018
	(5)		External Projection		AIS 147:2018
124	Refer Annexure-IA & IB	Safety standards of components as applicable		-	
125	(2)(a)	Rear View	Specifications		AIS-001 (Part 2) (Rev.1):2011
		Mirror	Installation		AIS-002 (Part 2) (Rev.1):2011

ICAT Ref No.	2023-0688; (IOCS Ref: 167837)
Power Test Report No.	CTOPR 0680 dt. 31.05.2022
Noise Report No.	CT0VS 1948 dt. 13.12.2023
Horn Inst. Report No.	CT0VS 1260 dt. 02.08.2023

**AUTHORISED SIGNATORY**

 <b>VIKAS SADAN</b> DEPUTY GENERAL MANAGER	 <b>ICAT</b> International Centre for Automotive Technology Innovation • Service • Excellence MANESAR	 <b>SAURABH DALELA</b> DIRECTOR	 Page 2 of 4
---	--	---	--