



C	A	T	B	0087
---	---	---	---	------

Date : 29th January 2024

ANNEXURE - I

Rule No.	Sub Rule(s)	Compliance Verified For		Standard	
93	(1)(A), (1)(B), (2)	Motor vehicle width, length and height		-	
94	(1), (2), (3)	Condition of tyres		-	
95	(1), (2), (3), (4), (5) & (6)	Size & ply rating of tyres		IS 15627:2005 & AIS-050-2004	
		Front/ Rear	Make		
			3.75-12, 66 B (Tube Type)		CEAT
			90/90-12, 54J (Tube Less)		TVS
90/90-12, 54J (Tube Type)	SPEEDWAYS				
		90/90-12, 54L (Tube Less)	RALSON		
96	(1), (2), (3), (4)(i), (7)(b)	Brakes		IS 14664:1999	
99	-	Forward and backward motion		-	
100	(1), (2), (3)	Safety glass		NA	
101	(1)	Windscreen Wiper		NA	
102	(1), (2)	Signaling devices, direction indicators and stop lights		-	
103	(1), (2)	Position of the indicator		-	
104	(1)(v), (4)	Fitment of reflectors & reflective tapes		AIS-057(Rev.1):2010 & AIS090-2005	
105	(1)(b), (3), (4), (5), (7)	Lamps		-	
106	(1)	Deflection of lights		-	
108	(1)	Use of red or white lights		-	
109	-	Parking lights		-	
110	-	Lamps for three wheelers		-	
111	-	Prohibition of spotlights etc.		-	
119	(1) & (2)	Horns	Installation		IS 15796:2008
			Limit :	83 dB(A) to 112 dB(A)	
			Observed :	93.1 dB(A)	
			Performance		IS 1884:1993
122	(1) & (2)	Embossment of chassis number & motor number & month of manufacture (Ref: Table 11 of the Technical Specifications)		AIS-065-2005	
124	-	Safety standards of components as applicable		Refer ANNEXURE - IA & IB	
125	(2)(a)	Rear View Mirror	Specifications		AIS-001 (Part-1)Rev.1:2011
			Installation		AIS-002 (Part-1)Rev.1:2011

ICAT Ref No.	2023-1460 (IOCS: 168019)
Power Test Report No.	CT0PL 0637 Dt.12.10.2016
Horn Inst. Report No.	CT0VL 0740 Dt.24.11.2016

AUTHORISED SIGNATORY			
JAYWANT HARDIKAR HEAD-CMVR		SAURBH DALELA DIRECTOR	Page 2 of 3