



C O T S 0438

Date : 30<sup>th</sup> April 2024

ANNEXURE - I

| Sr. No. | Trailer Nomenclature     | Overall Length (mm) | Wheel-base (mm) | Suspension Type* & GCW (kg)  | Unladen weight of trailer (kg) | Axle Spacing (m) |
|---------|--------------------------|---------------------|-----------------|------------------------------|--------------------------------|------------------|
| 1       | VTR-3FB-26FT-SKT-TRIDEM  | 8,100               | 5,125           | MMM - 55,000<br>MMM - 45,500 | 5,650                          | R1 to R3 < 3m    |
| 2       | VTR-3FB-28FT-FBT-TRIDEM  | 8,635               | 5,180           |                              | 6,200                          |                  |
| 3       | VTR-3FB-28FT-3SWT-TRIDEM | 8,635               | 5,180           |                              | 6,700                          |                  |
| 4       | VTR-3FB-28FT-4SWT-TRIDEM | 8,635               | 5,180           |                              | 6,850                          |                  |
| 5       | VTR-3FB-30FT-FBT-TRIDEM  | 9,245               | 5,790           |                              | 6,390                          |                  |
| 6       | VTR-3FB-30FT-3SWT-TRIDEM | 9,245               | 5,790           |                              | 7,140                          |                  |
| 7       | VTR-3FB-30FT-4SWT-TRIDEM | 9,245               | 5,790           |                              | 7,190                          |                  |
| 8       | VTR-3FB-30FT-5SWT-TRIDEM | 9,245               | 5,790           |                              | 7,345                          |                  |
| 9       | VTR-3FB-30FT-6SWT-TRIDEM | 9,245               | 5,790           |                              | 7,470                          |                  |
| 10      | VTR-3FB-32FT-3SWT-TRIDEM | 9,855               | 6,400           |                              | 7,310                          |                  |
| 11      | VTR-3FB-32FT-4SWT-TRIDEM | 9,855               | 6,400           |                              | 7,570                          |                  |
| 12      | VTR-3FB-32FT-5SWT-TRIDEM | 9,855               | 6,400           |                              | 7,580                          |                  |
| 13      | VTR-3FB-32FT-6SWT-TRIDEM | 9,855               | 6,400           |                              | 7,690                          |                  |
| 14      | VTR-3FB-34FT-3SWT-TRIDEM | 10,465              | 6,820           |                              | 7,540                          |                  |
| 15      | VTR-3FB-34FT-4SWT-TRIDEM | 10,465              | 6,820           |                              | 7,730                          |                  |
| 16      | VTR-3FB-34FT-5SWT-TRIDEM | 10,465              | 6,820           |                              | 7,940                          |                  |
| 17      | VTR-3FB-34FT-6SWT-TRIDEM | 10,465              | 6,820           |                              | 8,090                          |                  |

M-Mechanical, 1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt.16th July, 2018 with S.O. 3881(E) dt. 06th August, 2018.

MMM - Tridem mechanical suspended axles

R1, R2 & R3 - Trailer Rear Axles

AUTHORISED SIGNATORY

JAYWANT HARDIKAR  
HEAD-CMVR



SAURBH DALELA  
DIRECTOR

