



C A K D 0156 F02

Date : 15th May 2024

ANNEXURE - II

Standards	Notification	Date	Effective From	Applicable CMVR
CMVR Rule Inclusion of Category 'A'	GSR 111(E)	10.02.2004	Notified Dates	ANNEXURE - I/ ANNEXURE - IA/ ANNEXURE - IB
Safety Components	G.S.R. 589 (E)	16.09.2005		
Category of Vehicles-"A" / Horn/ Lighting and light Signaling Devices/ Retro Reflectors etc and safety components.	G.S.R. 784 (E)	12.11.2008		
	G.S.R 880 (E)	14.09.2016		
Tell- tale and Indicators	SO 436(E)	15.03.2012		
RVM Installation & Driver's Field of Vision	G.S.R 664 (E)	27.09.2013		
Driver & Bystander Noise/VIN/Bulbs/Fuel Tank & Maximum Speed	G.S.R 291(E)	24.04.2014		
Brakes for Agricultural Tractor,Steering Gears for Agricultural Tractors & Exhaust gases	GSR 1461(E)	27.11.2017		
Safety standards of components for agricultural tractor Reflex Reflector,Automobiles lamps & bulbs, Mechanical Couplings,Front Coupling Device (If Fitted)	GSR 1192(E)	10.12.2018		
Overall dimensions of Agricultural Tractor	GSR 414 (E)	26.06.2020		
Exhaust gases and exhaust pipes	GSR 240 (E)	31.03.2021		

ANNEXURE - III

Sr. No.	Variants	Max. PTO Power	Rated PTO Power	Type & Category
1	DI-42 HDM POWER PLUS	30.6 kW @ 1800 engine rpm	30.6 kW @ 1800 engine rpm	4 Wheeled, Rear Wheel Driven, General Purpose, Standard Agricultural tractor
2	DI-45			
3	DI-745 Ef			
4	DI-35 HDM POWER PLUS S2			
5	DI-42 HDM 4WD POWER			4 Wheeled, Four Wheel Driven, General Purpose, Standard Agricultural tractor
6	DI-45 4WD			
7	DI-745 4WD Ef			
8	DI-35 HDM 4WD POWER PLUS S2			

Size & ply rating of tyres for agricultural tractors			Make
Front	Base & Variant 1, 2, 3 & 4: 6.00 - 16, 6.8 PR Optional 1: 6.50- 16, 8PR Optional 2: 6.50- 20, 8PR Optional 3: 7.50 - 16, 8 PR	Variant 5, 6, 7 & 8: 8.00 - 18, 6 PR / 8 PR / 4PR Optional 1: 8.3 - 20, 6 PR / 8PR / 4PR / 12PR Optional 2: 8.3 - 24, 6 PR / 8PR / 4PR / 12PR Optional 3: 9.50-20, 8PR / 12 PR / 4PR / 6 PR	GOODYEAR / MRF / APOLLO / JK / CEAT / BKT / BIRLA

AUTHORISED SIGNATORY

JAYWANT HARDIKAR HEAD-CMVR		SAURABH DALELA DIRECTOR	Page 4 of 4