



C A O D 0568

Date : 05th June 2024

ANNEXURE - II

| Standards | Notification | Date | Effective From | Applicable CMVR |
|---|----------------|------------|----------------|--|
| CMVR Rule Inclusion of Category 'A' | GSR 111(E) | 10.02.2004 | Notified Dates | ANNEXURE - I/ ANNEXURE - IA/ ANNEXURE - IB |
| Safety Components | G.S.R. 589 (E) | 16.09.2005 | | |
| Category of Vehicles-"A" / Horn/ Lighting and light Signaling Devices/ Retro Réflectors etc and safety components. | G.S.R. 784 (E) | 12.11.2008 | | |
| | G.S.R 880 (E) | 14.09.2016 | | |
| Tell-tale and Indicators | SO 436(E) | 15.03.2012 | | |
| Protective structure(if fitted),Ballast mass,Load platform(if fitted), Attendant's Seat (If Fitted), Driver's Field of Vision | G.S.R 625 (E) | 08.08.2012 | | |
| RVM Installation & Driver's Field of Vision | G.S.R 664 (E) | 27.09.2013 | | |
| Driver & Bystander Noise/VIN/Bulbs/Fuel Tank & Maximum Speed | G.S.R 291(E) | 24.04.2014 | | |
| Brakes for Agricultural Tractor,Steering Gears for Agricultural Tractors | GSR 1461(E) | 27.11.2017 | | |
| Safety standards of components for agricultural tractor Reflex Reflector,Automobiles lamps & bulbs,,Front Coupling Device (If Fitted) | GSR 1192(E) | 10.12.2018 | | |
| Overall dimensions of Agricultural Tractor | GSR 414 (E) | 26.06.2020 | | |
| Exhaust gases and exhaust pipes | GSR 240 (E) | 31.03.2021 | | |

ANNEXURE - III

| Sr. No. | Variant | Max. PTO Power | Rated PTO Power | Type |
|---------|--------------------|---------------------------|---------------------------|--|
| 1 | DI-47 HDM + 4WD S2 | 33.1 kW @ 1900 engine rpm | 33.1 kW @ 1900 engine rpm | 4 Wheeled, Four Wheel Driven, General Purpose, Standard Agricultural tractor |
| 2 | DI-47 HDM + | | | 4 Wheeled, Rear Wheel Driven, General Purpose, Standard Agricultural tractor |
| 3 | DI-47 HDM +S2 | | | 4 Wheeled, Rear Wheel Driven, General Purpose, Standard Agricultural tractor |

| Size & ply rating of tyres for agricultural tractors | | Make |
|--|---|--|
| Front | Base & Variant 1 : 9.5-20, 8PR/ 6PR / 12PR/ 4PR Opt: 8.3-24, 6 PR / 8PR / 4PR / 12PR 8.3-20, 6 PR / 8PR / 4PR / 12PR 9.5-24, 8PR/ 12PR / 6PR/ 4PR 8.0-18, 6 PR / 4PR / 8PR Variant 2 & 3 : 7.50-16, 08 PR Opt.: 6.50-16, 08 PR 6.50-20, 08 PR 6.00-16, 08 PR | MRF / GOODYEAR / APOLLO / JK / CEAT/ BKT |
| Rear | 14.9-28, 12PR Opt. : 13.6- 28, 12PR | |

*** END OF DOCUMENT ***

| AUTHORISED SIGNATORY | | | |
|-------------------------------|---|----------------------------|-------------|
| | | | |
| JAYWANT HARDIKAR HEAD-CMVR | INTERNATIONAL CENTRE FOR AUTOMOTIVE TECHNOLOGY ★ MANESAR ★ | SAURABH DALELA DIRECTOR | Page 4 of 4 |