



C A T N 0894

Date : 26th September 2024

ANNEXURE - I

Rule No.	Sub Rule(s)	Compliance Verified For		Standard	
93	(1)(A), (1)(B) & (2)	Motor Vehicle width, length & height		-	
94	(1), (2) & (3)	Condition of tyres		-	
95	(1), (2), (3), (4), (5) & (6) (Tubeless)	Size & ply rating of tyres		IS 15627:2005 & AIS-050:2004	
		Front	100/80-17M/C 52P		MRF
	Rear	140/70R17M/C 66H			
96	(1), (2), (3), (4)(b)), (4A), (7)(c) & (8)	Brakes with ABS		IS 14664:2010	
102	(1), (2) & (3)	Signaling devices, direction indicators and stop lights		-	
103	(1)	Position of the indicator		-	
104	(1) & (4)	Fitment of reflectors		AIS-057 (Rev. 1): 2010	
105	(1)(bb), (2)(i) & (4)	Lamps		-	
106	(1)	Deflection of lights		-	
108	(1)	Use of red or white lights		-	
111	-	Prohibition of spotlights etc.		-	
114	(1) & (2)	Exhaust gases and exhaust pipes		-	
115	(1), (2)(i) & (19)(i)	Emission of smoke, vapour, etc. from motor vehicle (Bharat Stage - VI (Including OBD II-B))		AIS-137	
117	(1) & (2)	Speedometer		IS 11827:2008	
119	(1) & (2)	Horns	Installation (Above 7kW)	IS: 15796:2008	
			Limit :		87 dB(A) to 112 dB(A)
			Observed :		76 dB(A)
			Performance	IS 1884:1993	
120	(1)	Silencers		-	
	(2)	Pass by Noise	Limit : 77 dB(A) (80 < cc ≤ 175) Observed : 72.2 dB(A)	IS 3028:1998	
122	(1) & (2)	Embossment of chassis number & engine number & month of manufacture (Ref: Table 11 of the Technical Specifications)		AIS-065:2005	
123	(1)	Pillion Hand Hold		IS 14495:1998	
	(2)	Footrest		AIS 148:2018	
	(4)	Stand		AIS 146:2018	
	(5)	External projection		AIS 147:2018	
124	Refer Annexure-IA & IB	Safety standards of components as applicable		-	
125	(2)(a)	Rear View Mirror	Specifications	AIS-001 (Part 2) (Rev.1):2011	
			Installation	AIS-002 (Part 2) (Rev.1):2011	

ICAT Ref No. 2024-0798; IOCS Ref:- 178105
Emission Report No. CT0PT 0649 dt. 24.09.2024
Noise Report No. CT0VR 1818 dt. 27.12.2022
Horn Inst. Report No. CT0VN 1788 dt. 30.11.2018
FTP Report No. CT0ES 0168 dt. 28.03.2023

AUTHORISED SIGNATORY





JAYWANT HARDIKAR HEAD-CMVR SAURABH DALELA DIRECTOR Page 2 of 4