



C A S N 1021

Date : 18th November 2024

ANNEXURE - I

Rule No.	Sub Rule(s)	Compliance Verified For		Standard	
93	(1)(A), (1)(B) & (2)	Motor Vehicle width, length & height		-	
94	(1), (2) & (3)	Condition of tyres		-	
95	(1), (2), (3), (4), (5) & (6) (Tubeless)	Size & ply rating of tyres		IS 15627:2005 & AIS-050:2004	
		Front	80/100-18 M/C 47P 80/100-17 M/C 46P		MRF/TVS/CEAT/ACE Tyre(CEAT)
		Rear	100/90-18 M/C 56P 130/70-17 M/C 62P		MRF/TVS
96	(1), (2), (3), (4)(b)), (4A), (7)(c) & (8)	Brakes with ABS		IS 14664:2010	
102	(1), (2) & (3)	Signaling devices, direction indicators and stop lights		-	
103	(1)	Position of the indicator		-	
104	(1) & (4)	Fitment of reflectors		AIS-057 (Rev. 1): 2010	
105	(1)(bb), (2)(i) & (4)	Lamps		-	
106	(1)	Deflection of lights		-	
108	(1)	Use of red or white lights		-	
111	-	Prohibition of spotlights etc.		-	
114	(1) & (2)	Exhaust gases and exhaust pipes		-	
115	(1), (2)(i) & (19)(i)	Emission of smoke, vapour, etc. from motor vehicle		AIS-137	
117	(1) & (2)	Speedometer		IS 11827:2008	
119	(1) & (2)	Horns	Installation (Above 7kW)	IS-15796:2008	
			Limit :		87 dB(A) to 112 dB(A)
			Observed :		99.9 dB(A) & 96.6 dB(A)
		Performance	IS 1884:1993		
120	(1) (2)	Pass by Noise	Limit :	IS 3028:1998	
			Observed :		77 dB(A) (80 < cc ≤ 175) 72 dB(A)
122	(1) & (2)	Embossment of chassis number & engine number & month of manufacture (Ref: Table 11 of the Technical Specifications)		AIS-065:2005	
123	(1)	Pillion Hand Hold		IS 14495:1998	
	(2)	Footrest		AIS 148:2018	
	(4)	Stand		AIS 146:2018	
	(5)	External projection		AIS 147:2018	
124	Refer Annexure-IA & IB	Safety standards of components as applicable		-	
125	(2)(a)	Rear View Mirror	Specifications	AIS-001 (Part 2) (Rev.1):2011	
			Installation	AIS-002 (Part 2) (Rev.1):2011	

ICAT Ref No.	2024-1230; IOCS Ref:- 179601
Emission Report No.	CTOPT 0787 dt. 18.11.2024
Noise Report No.	CTOVT 1762 dt. 13.11.2024
Horn Inst. Report No.	CTOVTO 1307 dt. 05.12.2019 & CT0VP 0076 dt. 24.01.2020
FTP Report No.	CTOET 0437 dt. 12.11.2024

AUTHORISED SIGNATORY

--	--	--	--