



C A P A 0078 V01

**ANNEXURE - I**

Date : 28<sup>th</sup> January 2025

Rule No.	Sub Rule(s)	Compliance Verified For		Standard	
93	(1)(A), (1)(B), (2) & (3)	Overall dimension of motor vehicles		-	
94	(1), (2) & (3)	Condition of tyres		-	
95	(1), (2), (3), (4), (5), (6) (Radial Ply & Cross Ply with tube)	<b>Size &amp; ply rating of tyres</b>		IS:15636-2012 & AIS:051 - 2004	
		Front (Single)	7.50X16- 16 PR		JK, APOLLO, CEAT & MRF
			7.50R 16-16PR		
		Rear (Dual)	8.25 X16-16PR		
8.25 R16-16PR					
(1A)	Rolling Resistance, Wet Grip & Rolling Sound Emissions		AIS 142:2019		
96	(1), (2), (3), (4)(ii),	Brakes with ABS		IS:11852 - 2013	
98	(1), (2), (3)	Steering Gear		IS:11948 -2010	
				IS:12222 - 2011	
99	-	Forward and backward motion		-	
100	(1), (2), (3) & (3c)	Safety glass		IS 2553 (Part 2): (Revision 1): 2019	
101	(1) & (2)	Windscreen wiper		IS.15802:2008	
102	(1) & (2)	Signalling devices, direction indicators and stop lights		-	
103	(1) & (2)	Position of the indicator		-	
104	(1) & (4)	Fitment of reflectors		AIS:057 (Rev. 1)- 2010	
105	(1) (a), (2), (3), (4) & (7)	Lamps		-	
106	(1)	Deflection of lights		-	
108	(1)	Use of red or white lights		-	
109	-	Parking light		-	
111	-	Prohibition of spotlights etc.		-	
114	(1) & (2)	Exhaust gases and exhaust pipes		-	
115	(1), (2)(ii) & 18(ii)	Emission of smoke, vapour, etc. from motor vehicle (Including OBD II)		AIS-137 (Part 4)	
115B	B.I	Mass Emission standard for CNG Vehicles. For O.E. CNG Dedicated Vehicle made by vehicle manufacturers		-	
	E	CNG Safety Checks for CNG kit components and installation on the vehicle. As per AIS 028 and Gas Cylinder Rules, 2016.		-	
117	(1) & (2)	Speedometer		IS:11827-2008	
118	(1) & (2)	Speed Governor (SLF) (ECU- AFS Canada , ID- 20-05036)		AIS:018 - 2001	

**ICAT Ref No.** 2024-1546 (I/OCS Ref: 182137)

**Engine Test Report No.** CT0ES0023 E01 dt 03.05.2024 (OBD II)

**Noise Test Report No.** CT0VP 0122 DT: 04.02.2020 & CT0VT1766 dt. 13.11.2024

**Horn Inst. Test Report No.** ARAI/SHL/CT/APX-1011-2404/387 dt. 20.12.2010

**AUTHORISED SIGNATORY**





