



C O U S 0174

Date : 19th February 2025

ANNEXURE - I

Sr. No.	Trailer Nomenclature	Overall Length (mm)	Wheel-base (mm)	Suspension Type* & GCW (kg)	Unladen weight of trailer (kg)	Axle Spacing (m)
1	ISM TRI FB 26FT 45.5T	8,000	5,100	MMM - 45,500	6,110	R1 to R3 < 3m
2	ISM TRI SKT 26FT 45.5T	8,000	5,100		5,010	
3	ISM TRI SW 26FT 45.5T	8,000	5,100		6,500	
4	ISM TRI FB 28FT 45.5T	8,550	5,590		6,430	
5	ISM TRI SKT 28FT 45.5T	8,550	5,590		5,300	
6	ISM TRI SW 28FT 45.5T	8,550	5,590		6,800	
7	ISM TRI FB 30FT 45.5T	9,170	5,765		6,750	
8	ISM TRI SKT 30FT 45.5T	9,170	5,765		5,590	
9	ISM TRI SW 30FT 45.5T	9,170	5,765		7,100	
10	ISM TRI FB 32FT 45.5T	9,780	6,225		7,090	
11	ISM TRI SKT 32FT 45.5T	9,780	6,225		5,960	
12	ISM TRI SW 32FT 45.5T	9,780	6,225		7,460	
13	ISM TRI FB 34FT 45.5T	10,390	6,925		7,440	
14	ISM TRI SKT 34FT 45.5T	10,390	6,925		6,350	
15	ISM TRI SW 34FT 45.5T	10,390	6,925		7,840	
16	ISM TRI FB 36FT 45.5T	11,100	7,245		7,810	
17	ISM TRI SKT 36FT 45.5T	11,100	7,245		6,765	
18	ISM TRI SW 36FT 45.5T	11,100	7,245		8,480	

*A-Air, M-Mechanical, 1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt. 16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018.

R1, R2 & R3 - Trailer Rear Axles**AUTHORISED SIGNATORY**JAYWANT HARDIKAR
HEAD-CMVRSAURABH DALELA
DIRECTOR