



C A U N 0321

Date : 24th March 2025

ANNEXURE - I

Rule No.	Sub Rule(s)	Compliance Verified For		Standard
93	(1)(A), (1)(B) & (2)	Motor Vehicle width, length & height		-
94	(1), (2) & (3)	Condition of tyres		-
95	(1), (2), (3), (4), (5) & (6) (Crossply , Tubeless,Radial)	Size & ply rating of tyres		IS 15627:2005 & AIS-050:2004
		Front	100/80-17 M/C 52P	
		Rear	130/70 R 17 M/C 62P	
96	(1), (2), (3), (4)(b)), (4A), (7)(c) & (8)	Brakes with ABS		IS 14664:2010
102	(1), (2) & (3)	Signaling devices, direction indicators and stop lights		-
103	(1)	Position of the indicator		-
104	(1) & (4)	Fitment of reflectors		AIS-057 (Rev. 1): 2010
105	(1)(bb), (2)(i) & (4)	Lamps		-
106	(1)	Deflection of lights		-
108	(1)	Use of red or white lights		-
111	-	Prohibition of spotlights etc.		-
114	(1) & (2)	Exhaust gases and exhaust pipes		-
115	(1), (2)(i) & (19)(i)	Emission of smoke, vapour, etc. from motor vehicle (Bharat Stage - VI (Including OBD STAGE II-B) (E20))		AIS-137
117	(1) & (2)	Speedometer		IS 11827:2008
119	(1) & (2)	Horns	Installation (Above 7kW)	IS 15796:2008 (Amd. No.3 2019)
			Limit : 87 dB(A) to 112 dB(A)	
			Observed : 100.7 / 98.9 / 100.8 dB(A)	
120	(1) (2)	Pass by Noise	Performance	IS 1884:1993
			Silencers	-
			Limit : 77 dB(A) (≤ 175)	IS 3028:1998
122	(1) & (2)	Embossment of chassis number & engine number & month of manufacture (Ref: Table 11 of the Technical Specifications)	Observed : 73.0 dB(A)	
123	(1)	Pillion Hand Hold		IS 14495:1998
	(2)	Footrest		AIS 148:2018
	(4)	Stand		AIS 146:2018
	(5)	External projection		AIS 147:2018
124	Refer Annexure-IA & IB	Safety standards of components as applicable		-
125	(2)(a)	Rear View Mirror	Specifications	AIS-001 (Part 2) (Rev.1):2011
			Installation	AIS-002 (Part 2) (Rev.1):2011

ICAT Ref No. 2024-2055; IOCS: 184343

Emission Report No. CT0PU 0355 Dt. 24.03.2025

Noise Report No. CT1VU 0523 Dt. 24.03.2025

Horn Inst. Report No. CT0VP 0258 Dt. 05.03.2020

FTP Report No. CT0EU 0178 Dt. 24.03.2025

AUTHORISED SIGNATORY

JAYWANT HARDIKAR
HEAD-CMVR



SAURABH DALELA
DIRECTOR

