

ANNEXURE - I

Sr. No.	Trailer Nomenclature	Overall Length (mm)	Wheel-base (mm)	Suspension Type* & GCW (kg)	Unladen weight of trailer (kg)	Axle Spacing (m)
1	ITS-3FB-26FT-SKT-3IA	7,925	4,900	MMM - 53,000 AMM - 54,000 AAA - 55,000	4,620	R1 to R3 > 3m
2	ITS-3FB-26FT-FBT-3IA	7,925	4,900		5,520	
3	ITS-3FB-28FT-SKT-3IA	8,550	5,460		4,735	
4	ITS-3FB-28FT-FBT-3IA	8,550	5,460		5,690	
5	ITS-3FB-28FT-SBT-3IA	8,550	5,460		6,495	
6	ITS-3FB-30FT-SKT-3IA	9,145	5,915		4,845	
7	ITS-3FB-30FT-FBT-3IA	9,145	5,915		5,860	
8	ITS-3FB-30FT-SBT-3IA	9,145	5,915		6,720	
9	ITS-3FB-32FT-SKT-3IA	9,754	6,464		4,930	
10	ITS-3FB-32FT-FBT-3IA	9,754	6,464		6,020	
11	ITS-3FB-32FT-SBT-3IA	9,754	6,464		6,930	
12	ITS-3FB-34FT-SKT-3IA	10,363	7,020		5,100	
13	ITS-3FB-34FT-FBT-3IA	10,363	7,020		6,250	
14	ITS-3FB-34FT-SBT-3IA	10,363	7,020		7,215	
15	ITS-3FB-36FT-SKT-3IA	10,973	7,583		5,220	
16	ITS-3FB-36FT-FBT-3IA	10,973	7,583		6,430	
17	ITS-3FB-36FT-SBT-3IA	10,973	7,583		7,430	
18	ITS-3FB-38FT-SKT-3IA	11,583	7,950		5,320	

*A-Air, M-Mechanical, 1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt. 16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018.

R1, R2 & R3 - Trailer Rear Axles**AUTHORISED SIGNATORY**

JAYWANT HARDIKAR HEAD-CMVR		SAURABH DALELA DIRECTOR	Page 2 of 8

ANNEXURE - I

Sr. No.	Trailer Nomenclature	Overall Length (mm)	Wheel-base (mm)	Suspension Type* & GCW (kg)	Unladen weight of trailer (kg)	Axle Spacing (m)
19	ITS-3FB-38FT-FBT-3IA	11,583	7,950	MMM - 53,000 AMM - 54,000 AAA - 55,000	6,550	R1 to R3 > 3m
20	ITS-3FB-38FT-SBT-3IA	11,583	7,950		7,580	
21	ITS-3FB-40FT-SKT-3IA	12,192	8,452		5,450	
22	ITS-3FB-40FT-FBT-3IA	12,192	8,452		6,820	
23	ITS-3FB-40FT-SBT-3IA	12,192	8,452		7,910	
24	ITS-3FB-42FT-SKT-3IA	12,805	8,900		5,650	
25	ITS-3FB-42FT-FBT-3IA	12,805	8,900		7,050	
26	ITS-3FB-42FT-SBT-3IA	12,805	8,900		8,150	
27	ITS-3FB-45FT-SKT-3IA	13,716	9,350		6,050	
28	ITS-3FB-45FT-FBT-3IA	13,716	9,290		7,410	
29	ITS-3FB-45FT-SBT-3IA	13,716	9,350		8,540	
30	ITS-3FB-31FT-SBT-3IA	9,470	6,270		6,825	
31	ITS-3FB-33FT-SBT-3IA	10,060	6,660		7,075	
32	ITS-3FB-35FT-SBT-3IA	10,690	7,240		7,325	
33	ITS-3FB-28FT-SKT-2+1A	8,550	6,110	MMM - 51,000 AMM - 52,000 AAA - 54,000	4,735	R1 to R3 > 3m & R2 to R3 < 1.8m
34	ITS-3FB-28FT-FBT-2+1A	8,550	6,110		5,690	
35	ITS-3FB-28FT-SBT-2+1A	8,550	6,110		6,495	
36	ITS-3FB-30FT-SKT-2+1A	9,145	6,565		4,845	

*A-Air, M-Mechanical, 1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt. 16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018.

R1, R2 & R3 - Trailer Rear Axles**AUTHORISED SIGNATORY**

JAYWANT HARDIKAR HEAD-CMVR		SAURABH DALELA DIRECTOR	Page 3 of 8

ANNEXURE - I

Sr. No.	Trailer Nomenclature	Overall Length (mm)	Wheel-base (mm)	Suspension Type* & GCW (kg)	Unladen weight of trailer (kg)	Axle Spacing (m)
37	ITS-3FB-30FT-FBT-2+1A	9,145	6,565	MMM - 51,000 AMM - 52,000 AAA - 54,000	5,860	R1 to R3 > 3m & R2 to R3 < 1.8m
38	ITS-3FB-30FT-SBT-2+1A	9,145	6,565		6,720	
39	ITS-3FB-32FT-SKT-2+1A	9,754	7,114		4,930	
40	ITS-3FB-32FT-FBT-2+1A	9,754	7,114		6,020	
41	ITS-3FB-32FT-SBT-2+1A	9,754	7,114		6,930	
42	ITS-3FB-34FT-SKT-2+1A	10,363	7,670		5,100	
43	ITS-3FB-34FT-FBT-2+1A	10,363	7,670		6,250	
44	ITS-3FB-34FT-SBT-2+1A	10,363	7,670		7,215	
45	ITS-3FB-36FT-SKT-2+1A	10,973	8,233		5,220	
46	ITS-3FB-36FT-FBT-2+1A	10,973	8,233		6,430	
47	ITS-3FB-36FT-SBT-2+1A	10,973	8,233		7,430	
48	ITS-3FB-38FT-SKT-2+1A	10,903	8,600		5,320	
49	ITS-3FB-38FT-FBT-2+1A	10,903	8,600		6,550	
50	ITS-3FB-38FT-SBT-2+1A	10,903	8,600		7,580	
51	ITS-3FB-40FT-SKT-2+1A	11,512	9,102		5,450	
52	ITS-3FB-40FT-FBT-2+1A	11,512	9,102		6,820	
53	ITS-3FB-40FT-SBT-2+1A	11,512	9,102		7,910	
54	ITS-3FB-42FT-SKT-2+1A	11,905	9,550		5,650	

*A-Air, M-Mechanical, 1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt. 16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018.

R1, R2 & R3 - Trailer Rear Axles**AUTHORISED SIGNATORY**

JAYWANT HARDIKAR HEAD-CMVR		SAURABH DALELA DIRECTOR	Page 4 of 8

ANNEXURE - I

Sr. No.	Trailer Nomenclature	Overall Length (mm)	Wheel-base (mm)	Suspension Type* & GCW (kg)	Unladen weight of trailer (kg)	Axle Spacing (m)
55	ITS-3FB-42FT-FBT-2+1A	11,905	9,550	MMM - 51,000 AMM - 52,000 AAA - 54,000	7,050	R1 to R3 > 3m & R2 to R3 < 1.8m
56	ITS-3FB-42FT-SBT-2+1A	11,905	9,550		8,150	
57	ITS-3FB-45FT-SKT-2+1A	12,816	9,950		6,050	
58	ITS-3FB-45FT-FBT-2+1A	12,816	9,950		7,410	
59	ITS-3FB-45FT-SBT-2+1A	12,816	9,950		8,540	
60	ITS-3FB-31FT-SBT-2+1A	8,720	6,930		6,825	
61	ITS-3FB-33FT-SBT-2+1A	9,310	7,040		7,075	
62	ITS-3FB-35FT-SBT-2+1A	9,940	7,318		7,325	
63	ITS-3FB-24FT-SKT-3A-550FOH	7,320	4,650	MMM - 45,500 AAA - 48,500 MMM - 55,000 AAA - 55,000	4,510	R1 to R3 < 3m
64	ITS-3FB-24FT-FBT-3A-550FOH	7,320	4,650		5,350	
65	ITS-3FB-26FT-SKT-3A-600FOH	7,925	4,900		4,620	
66	ITS-3FB-26FT-FBT-3A-600FOH	7,925	4,900		5,520	
67	ITS-3FB-28FT-SKT-3A-680FOH	8,550	5,460		4,735	
68	ITS-3FB-28FT-FBT-3A-680FOH	8,550	5,460		5,690	
69	ITS-3FB-28FT-SBT-3A-680FOH	8,550	5,460		6,496	
70	ITS-3FB-30FT-SKT-3A-680FOH	9,145	5,915		4,845	
71	ITS-3FB-30FT-FBT-3A-680FOH	9,145	5,915		5,860	
72	ITS-3FB-30FT-SBT-3A-680FOH	9,145	5,915		6,720	

*A-Air, M-Mechanical, 1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt. 16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018.

R1, R2 & R3 - Trailer Rear Axles**AUTHORISED SIGNATORY**

JAYWANT HARDIKAR HEAD-CMVR		SAURABH DALELA DIRECTOR	Page 5 of 8

ANNEXURE - I

Sr. No.	Trailer Nomenclature	Overall Length (mm)	Wheel-base (mm)	Suspension Type* & GCW (kg)	Unladen weight of trailer (kg)	Axle Spacing (m)
73	ITS-3FB-32FT-SKT-3A-680FOH	9,754	6,464	MMM - 45,500 AAA - 48,500 MMM - 55,000 AAA - 55,000	4,930	R1 to R3 < 3m
74	ITS-3FB-32FT-FBT-3A-680FOH	9,754	6,464		6,020	
75	ITS-3FB-32FT-SBT-3A-680FOH	9,754	6,464		6,930	
76	ITS-3FB-34FT-SKT-3A-680FOH	10,363	7,020		5,100	
77	ITS-3FB-34FT-FBT-3A-680FOH	10,363	7,020		6,250	
78	ITS-3FB-34FT-SBT-3A-680FOH	10,363	7,020		7,215	
79	ITS-3FB-36FT-SKT-3A-680FOH	10,973	7,583		5,220	
80	ITS-3FB-36FT-FBT-3A-680FOH	10,973	7,583		6,430	
81	ITS-3FB-36FT-SBT-3A-680FOH	10,973	7,583		7,430	
82	ITS-3FB-38FT-SKT-3A-680FOH	11,583	7,950		5,320	
83	ITS-3FB-38FT-FBT-3A-680FOH	11,583	7,950		6,550	
84	ITS-3FB-38FT-SBT-3A-680FOH	11,583	7,950		7,580	
85	ITS-3FB-40FT-SKT-3A-680FOH	12,192	8,452		5,450	
86	ITS-3FB-40FT-FBT-3A-680FOH	12,192	8,452		6,820	
87	ITS-3FB-40FT-SBT-3A-680FOH	12,192	8,452		7,910	
88	ITS-3FB-42FT-SKT-3A-900FOH	12,805	8,900		5,650	
89	ITS-3FB-42FT-FBT-3A-900FOH	12,805	8,900		7,050	
90	ITS-3FB-42FT-SBT-3A-900FOH	12,805	8,900		8,150	

*A-Air, M-Mechanical, 1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt. 16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018.

R1, R2 & R3 - Trailer Rear Axles**AUTHORISED SIGNATORY**

JAYWANT HARDIKAR HEAD-CMVR		SAURABH DALELA DIRECTOR	Page 6 of 8

ANNEXURE - I

Sr. No.	Trailer Nomenclature	Overall Length (mm)	Wheel-base (mm)	Suspension Type* & GCW (kg)	Unladen weight of trailer (kg)	Axle Spacing (m)
91	ITS-3FB-45FT-SKT-3A-900FOH	13,716	9,350	MMM - 45,500 AAA - 48,500 MMM - 55,000 AAA - 55,000	6,050	R1 to R3 < 3m
92	ITS-3FB-45FT-FBT-3A-900FOH	13,716	9,350		7,370	
93	ITS-3FB-45FT-SBT-3A-900FOH	13,716	9,350		8,540	
94	ITS-3FB-31FT-SBT-3A-750FOH	9,470	6,270		6,825	
95	ITS-3FB-33FT-SBT-3A-750FOH	10,060	6,660		7,075	
96	ITS-3FB-35FT-SBT-3A-750FOH	10,690	7,240		7,325	
97	ITS-3FB-28FT-SKT-3A-1200FOH	8,550	4,950	MMM - 55,000 AAA - 55,000	4,735	
98	ITS-3FB-28FT-FBT-3A-1200FOH	8,550	4,950		5,690	
99	ITS-3FB-28FT-SBT-3A-1200FOH	8,550	4,950		6,495	
100	ITS-3FB-30FT-SKT-3A-1200FOH	9,145	5,545		4,845	
101	ITS-3FB-30FT-FBT-3A-1200FOH	9,145	5,545		5,860	
102	ITS-3FB-30FT-SBT-3A-1200FOH	9,145	5,545		6,720	
103	ITS-3FB-32FT-SKT-3A-1250FOH	9,754	6,102		4,930	
104	ITS-3FB-32FT-FBT-3A-1250FOH	9,754	6,102		6,020	
105	ITS-3FB-32FT-SBT-3A-1250FOH	9,754	6,102		6,930	
106	ITS-3FB-34FT-SKT-3A-1250FOH	10,363	6,658		5,100	
107	ITS-3FB-34FT-FBT-3A-1250FOH	10,363	6,658		6,250	
108	ITS-3FB-34FT-SBT-3A-1250FOH	10,363	6,658		7,215	

*A-Air, M-Mechanical, 1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt. 16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018.

R1, R2 & R3 - Trailer Rear Axles**AUTHORISED SIGNATORY**

JAYWANT HARDIKAR HEAD-CMVR		SAURABH DALELA DIRECTOR	Page 7 of 8

ANNEXURE - I

Sr. No.	Trailer Nomenclature	Overall Length (mm)	Wheel-base (mm)	Suspension Type* & GCW (kg)	Unladen weight of trailer (kg)	Axle Spacing (m)
109	ITS-3FB-36FT-SKT-3A-1250FOH	10,973	7,221	MMM - 55,000 AAA - 55,000	5,220	R1 to R3 < 3m
110	ITS-3FB-36FT-FBT-3A-1250FOH	10,973	7,221		6,430	
111	ITS-3FB-36FT-SBT-3A-1250FOH	10,973	7,221		7,430	
112	ITS-3FB-38FT-SKT-3A-1250FOH	11,583	7,600		5,320	
113	ITS-3FB-38FT-FBT-3A-1250FOH	11,583	7,600		6,550	
114	ITS-3FB-38FT-SBT-3A-1250FOH	11,583	7,600		7,580	
115	ITS-3FB-40FT-SKT-3A-1250FOH	12,192	8,090		5,450	
116	ITS-3FB-40FT-FBT-3A-1250FOH	12,192	8,090		6,820	
117	ITS-3FB-40FT-SBT-3A-1250FOH	12,192	8,090		7,910	
118	ITS-3FB-42FT-SKT-3A-1250FOH	12,805	8,620		5,650	
119	ITS-3FB-42FT-FBT-3A-1250FOH	12,805	8,620		7,050	
120	ITS-3FB-42FT-SBT-3A-1250FOH	12,805	8,620		8,150	
121	ITS-3FB-45FT-SKT-3A-1250FOH	13,716	9,150		6,050	
122	ITS-3FB-45FT-FBT-3A-1250FOH	13,716	9,150		7,370	
123	ITS-3FB-45FT-SBT-3A-1250FOH	13,716	9,150		8,540	

*A-Air, M-Mechanical, 1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt. 16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018.

R1, R2 & R3 - Trailer Rear Axles

**** END OF DOCUMENT ****

AUTHORISED SIGNATORY			
JAYWANT HARDIKAR HEAD-CMVR		SAURABH DALELA DIRECTOR	Page 8 of 8