

ANNEXURE - I

Sr. No.	Trailer Nomenclature	Overall Length (mm)	Wheel-base (mm)	Suspension Type* & GCW (kg)	Unladen weight of trailer (kg)	Axle Spacing (m)
1	BEW 28CUM TIPPER 550 FOH	8,310	5,198	MMM - 55,000	9,600	R1 to R3 < 3m
2	BEW 32CUM TIPPER 550 FOH	8,610	5,420		9,800	
3	BEW 34CUM TIPPER 550 FOH	8,610	5,480		10,000	
4	BEW 36CUM TIPPER 710 FOH	8,730	5,565		10,010	
5	BEW 30CUM TIPPER 550 FOH	8,610	6,148	AMM - 52,000	10,660	R1 to R3 > 3m & R2 to R3 < 1.8m
6	BEW 32CUM TIPPER 550 FOH	8,650	6,453		11,770	
7	BEW 34CUM TIPPER 550 FOH	8,700	6,115		12,660	
8	BEW 28CUM TIPPER 550 FOH	8,520	5,380	AMM - 54,000	10,660	R1 to R3 > 3m
9	BEW 32CUM TIPPER 550 FOH	8,610	5,420		11,770	
10	BEW 34CUM TIPPER 550 FOH	8,700	5,480		12,660	
11	BEW 36CUM TIPPER 610 FOH	8,725	5,500		12,900	

*A-Air, M-Mechanical, 1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt. 16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018.

R1, R2 & R3 - Trailer Rear Axles

**** END OF DOCUMENT ****

AUTHORISED SIGNATORY		
JAYWANT HARDIKAR HEAD-CMVR	SAURABH DALELA DIRECTOR	Page 2 of 2