

ANNEXURE - I

Sr. No.	Trailer Nomenclature	Overall Length (mm)	Wheel-base (mm)	Suspension Type* & GCW (kg)	Unladen weight of trailer (kg)	Axle Spacing (m)
1	LTE-3FB-26FT-SKT-3A-600FOH	7,925	4,900	MMM - 45,500 AAA - 48,500 MMM - 55,000 AAA - 55,000	4,620	R1 to R3 < 3m
2	LTE-3FB-26FT-FBT-3A-600FOH	7,925	4,900		5,520	
3	LTE-3FB-28FT-SKT-3A-680FOH	8,550	5,460		4,735	
4	LTE-3FB-28FT-FBT-3A-680FOH	8,550	5,460		5,690	
5	LTE-3FB-28FT-SBT-3A-680FOH	8,550	5,460		6,500	
6	LTE-3FB-30FT-SKT-3A-680FOH	9,145	5,915		4,850	
7	LTE-3FB-30FT-FBT-3A-680FOH	9,145	5,915		5,860	
8	LTE-3FB-30FT-SBT-3A-680FOH	9,145	5,915		6,720	
9	LTE-3FB-32FT-SKT-3A-680FOH	9,754	6,464		4,930	
10	LTE-3FB-32FT-FBT-3A-680FOH	9,754	6,464		6,020	
11	LTE-3FB-32FT-SBT-3A-680FOH	9,754	6,464		6,940	
12	LTE-3FB-34FT-SKT-3A-680FOH	10,363	7,020		5,100	
13	LTE-3FB-34FT-FBT-3A-680FOH	10,363	7,020		6,250	
14	LTE-3FB-34FT-SBT-3A-680FOH	10,363	7,020		7,220	
15	LTE-3FB-36FT-SKT-3A-680FOH	10,973	7,583		5,220	
16	LTE-3FB-36FT-FBT-3A-680FOH	10,973	7,583		6,430	
17	LTE-3FB-36FT-SBT-3A-680FOH	10,973	7,583		7,430	
18	LTE-3FB-38FT-SKT-3A-680FOH	11,583	7,920		5,320	

*A-Air, M-Mechanical, 1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt. 16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018.

R1, R2 & R3 - Trailer Rear Axles
AUTHORISED SIGNATORY

JAYWANT HARDIKAR HEAD-CMVR	SAURABH DALELA DIRECTOR	Page 2 of 8

ANNEXURE - I

Sr. No.	Trailer Nomenclature	Overall Length (mm)	Wheel-base (mm)	Suspension Type* & GCW (kg)	Unladen weight of trailer (kg)	Axle Spacing (m)	
19	LTE-3FB-38FT-FBT-3A-680FOH	11,583	7,950	MMM - 45,500 AAA - 48,500 MMM - 55,000 AAA - 55,000	6,550	R1 to R3 < 3m	
20	LTE-3FB-38FT-SBT-3A-680FOH	11,583	7,950		7,580		
21	LTE-3FB-40FT-SKT-3A-680FOH	12,192	8,452		5,450		
22	LTE-3FB-40FT-FBT-3A-680FOH	12,192	8,452		6,820		
23	LTE-3FB-40FT-SBT-3A-680FOH	12,192	8,452		7,910		
24	LTE-3FB-42FT-SKT-3A-900FOH	12,805	8,900		5,650		
25	LTE-3FB-42FT-FBT-3A-900FOH	12,805	8,900		7,050		
26	LTE-3FB-42FT-SBT-3A-900FOH	12,805	8,900		8,150		
27	LTE-3FB-44FT-SBT-3A-920FOH	13,460	9,470		9,170		
28	LTE-3FB-45FT-SKT-3A-900FOH	13,716	9,350		6,050		
29	LTE-3FB-45FT-FBT-3A-900FOH	13,716	9,350		7,370		
30	LTE-3FB-45FT-SBT-3A-900FOH	13,716	9,350		8,540		
31	LTE-3FB-28FT-SKT-3A-1200FOH	8,550	4,950		MMM - 55,000 AAA - 55,000		4,735
32	LTE-3FB-28FT-FBT-3A-1200FOH	8,550	4,950				5,690
33	LTE-3FB-28FT-SBT-3A-1200FOH	8,550	4,950	6,500			
34	LTE-3FB-30FT-SKT-3A-1200FOH	9,145	5,545	4,850			
35	LTE-3FB-30FT-FBT-3A-1200FOH	9,145	5,545	5,860			
36	LTE-3FB-30FT-SBT-3A-1200FOH	9,145	5,545	6,720			

*A-Air, M-Mechanical, 1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt. 16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018.

R1, R2 & R3 - Trailer Rear Axles

AUTHORISED SIGNATORY	
JAYWANT HARDIKAR HEAD-CMVR	SAURABH DALELA DIRECTOR

ANNEXURE - I

Sr. No.	Trailer Nomenclature	Overall Length (mm)	Wheel-base (mm)	Suspension Type* & GCW (kg)	Unladen weight of trailer (kg)	Axle Spacing (m)
37	LTE-3FB-32FT-SKT-3A-1250FOH	9,754	6,102	MMM - 55,000 AAA - 55,000	4,930	R1 to R3 < 3m
38	LTE-3FB-32FT-FBT-3A-1250FOH	9,754	6,102		6,020	
39	LTE-3FB-32FT-SBT-3A-1250FOH	9,754	6,102		6,935	
40	LTE-3FB-34FT-SKT-3A-1250FOH	10,363	6,658		5,100	
41	LTE-3FB-34FT-FBT-3A-1250FOH	10,363	6,658		6,250	
42	LTE-3FB-34FT-SBT-3A-1250FOH	10,363	6,658		7,230	
43	LTE-3FB-36FT-SKT-3A-1250FOH	10,973	7,221		5,220	
44	LTE-3FB-36FT-FBT-3A-1250FOH	10,973	7,221		6,430	
45	LTE-3FB-36FT-SBT-3A-1250FOH	10,973	7,221		7,430	
46	LTE-3FB-38FT-SKT-3A-1250FOH	11,583	7,600		5,320	
47	LTE-3FB-38FT-FBT-3A-1250FOH	11,583	7,600		6,550	
48	LTE-3FB-38FT-SBT-3A-1250FOH	11,583	7,600		7,580	
49	LTE-3FB-40FT-SKT-3A-1250FOH	12,192	8,090		5,450	
50	LTE-3FB-40FT-FBT-3A-1250FOH	12,192	8,090		6,820	
51	LTE-3FB-40FT-SBT-3A-1250FOH	12,192	8,090		7,910	
52	LTE-3FB-42FT-SKT-3A-1250FOH	12,805	8,620		5,650	
53	LTE-3FB-42FT-FBT-3A-1250FOH	12,805	8,620	7,050		
54	LTE-3FB-42FT-SBT-3A-1250FOH	12,805	8,620	8,150		

*A-Air, M-Mechanical, 1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt. 16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018.

R1, R2 & R3 - Trailer Rear Axles

AUTHORISED SIGNATORY		
JAYWANT HARDIKAR HEAD-CMVR		SAURABH DALELA DIRECTOR

ANNEXURE - I

Sr. No.	Trailer Nomenclature	Overall Length (mm)	Wheel-base (mm)	Suspension Type* & GCW (kg)	Unladen weight of trailer (kg)	Axle Spacing (m)
55	LTE-3FB-45FT-SKT-3A-1250FOH	13,716	9,150	MMM - 55,000 AAA - 55,000	6,050	R1 to R3 < 3m
56	LTE-3FB-45FT-FBT-3A-1250FOH	13,716	9,150		7,370	
57	LTE-3FB-45FT-SBT-3A-1250FOH	13,716	9,150		8,540	
58	LTE-3FB-28FT-SKT-2+1A	8,550	6,110	MMM - 51,000 AMM - 52,000 AAA - 54,000	4,735	R1 to R3 > 3m & R2 to R3 < 1.8 m
59	LTE-3FB-28FT-FBT-2+1A	8,550	6,110		5,690	
60	LTE-3FB-28FT-SBT-2+1A	8,550	6,110		6,500	
61	LTE-3FB-30FT-SKT-2+1A	9,145	6,565		4,850	
62	LTE-3FB-30FT-FBT-2+1A	9,145	6,565		5,860	
63	LTE-3FB-30FT-SBT-2+1A	9,145	6,565		6,720	
64	LTE-3FB-32FT-SKT-2+1A	9,754	7,114		4,930	
65	LTE-3FB-32FT-FBT-2+1A	9,754	7,114		6,020	
66	LTE-3FB-32FT-SBT-2+1A	9,754	7,114		6,940	
67	LTE-3FB-34FT-SKT-2+1A	10,363	7,670		5,100	
68	LTE-3FB-34FT-FBT-2+1A	10,363	7,670		6,350	
69	LTE-3FB-34FT-SBT-2+1A	10,363	7,670		7,220	
70	LTE-3FB-36FT-SKT-2+1A	10,973	8,233		5,220	
71	LTE-3FB-36FT-FBT-2+1A	10,973	8,233		6,430	
72	LTE-3FB-36FT-SBT-2+1A	10,973	8,233		7,430	

*A-Air, M-Mechanical, 1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt. 16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018.

R1, R2 & R3 - Trailer Rear Axles

AUTHORISED SIGNATORY		
JAYWANT HARDIKAR HEAD-CMVR	SAURABH DALELA DIRECTOR	Page 5 of 8

ANNEXURE - I

Sr. No.	Trailer Nomenclature	Overall Length (mm)	Wheel-base (mm)	Suspension Type* & GCW (kg)	Unladen weight of trailer (kg)	Axle Spacing (m)		
73	LTE-3FB-38FT-SKT-2+1A	11,583	8,600	MMM - 51,000 AMM - 52,000 AAA - 54,000	5,320	R1 to R3 > 3m & R2 to R3 < 1.8 m		
74	LTE-3FB-38FT-FBT-2+1A	11,583	8,600		6,550			
75	LTE-3FB-38FT-SBT-2+1A	11,583	8,600		7,580			
76	LTE-3FB-40FT-SKT-2+1A	12,192	9,102		5,450			
77	LTE-3FB-40FT-FBT-2+1A	12,192	9,102		6,820			
78	LTE-3FB-40FT-SBT-2+1A	12,192	9,102		7,910			
79	LTE-3FB-42FT-SKT-2+1A	12,805	9,550		5,650			
80	LTE-3FB-42FT-FBT-2+1A	12,805	9,550		7,050			
81	LTE-3FB-42FT-SBT-2+1A	12,805	9,550		8,150			
82	LTE-3FB-45FT-SKT-2+1A	13,716	9,950		6,050			
83	LTE-3FB-45FT-FBT-2+1A	13,716	9,950		7,370			
84	LTE-3FB-45FT-SBT-2+1A	13,716	9,950		8,540			
85	LTE-3FB-26FT-SKT-3IA	7,925	4,900		MMM - 53,000 AMM - 54,000 AAA - 55,000		4,620	R1 to R3 > 3m
86	LTE-3FB-26FT-FBT-3IA	7,925	4,900				5,520	
87	LTE-3FB-28FT-SKT-3IA	8,550	5,460	4,735				
88	LTE-3FB-28FT-FBT-3IA	8,550	5,460	5,690				
89	LTE-3FB-28FT-SBT-3IA	8,550	5,460	6,500				
90	LTE-3FB-30FT-SKT-3IA	9,145	5,915	4,850				

*A-Air, M-Mechanical, 1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt. 16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018.

R1, R2 & R3 - Trailer Rear Axles

AUTHORISED SIGNATORY		
JAYWANT HARDIKAR HEAD-CMVR	SAURABH DALELA DIRECTOR	Page 6 of 8

ANNEXURE - I

Sr. No.	Trailer Nomenclature	Overall Length (mm)	Wheel-base (mm)	Suspension Type* & GCW (kg)	Unladen weight of trailer (kg)	Axle Spacing (m)
91	LTE-3FB-30FT-FBT-3IA	9,145	5,915	MMM - 53,000 AMM - 54,000 AAA - 55,000	5,860	R1 to R3 > 3m
92	LTE-3FB-30FT-SBT-3IA	9,145	5,915		6,720	
93	LTE-3FB-32FT-SKT-3IA	9,754	6,464		4,930	
94	LTE-3FB-32FT-FBT-3IA	9,754	6,464		6,020	
95	LTE-3FB-32FT-SBT-3IA	9,754	6,464		6,940	
96	LTE-3FB-34FT-SKT-3IA	10,363	7,020		5,100	
97	LTE-3FB-34FT-FBT-3IA	10,363	7,020		6,250	
98	LTE-3FB-34FT-SBT-3IA	10,363	7,020		7,220	
99	LTE-3FB-36FT-SKT-3IA	10,973	7,583		5,220	
100	LTE-3FB-36FT-FBT-3IA	10,973	7,583		6,430	
101	LTE-3FB-36FT-SBT-3IA	10,973	7,583		7,430	
102	LTE-3FB-38FT-SKT-3IA	11,583	7,950		5,320	
103	LTE-3FB-38FT-FBT-3IA	11,583	7,950		6,550	
104	LTE-3FB-38FT-SBT-3IA	11,583	7,950		7,580	
105	LTE-3FB-40FT-SKT-3IA	12,192	8,452		5,450	
106	LTE-3FB-40FT-FBT-3IA	12,192	8,452		6,820	
107	LTE-3FB-40FT-SBT-3IA	12,192	8,452		7,910	
108	LTE-3FB-42FT-SKT-3IA	12,800	8,900		5,650	

*A-Air, M-Mechanical, 1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt. 16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018.

R1, R2 & R3 - Trailer Rear Axles

AUTHORISED SIGNATORY		
JAYWANT HARDIKAR HEAD-CMVR		SAURABH DALELA DIRECTOR

ANNEXURE - I

Sr. No.	Trailer Nomenclature	Overall Length (mm)	Wheel-base (mm)	Suspension Type* & GCW (kg)	Unladen weight of trailer (kg)	Axle Spacing (m)
109	LTE-3FB-42FT-FBT-3IA	12,800	8,900	MMM - 53,000 AMM - 54,000 AAA - 55,000	7,050	R1 to R3 > 3m
110	LTE-3FB-42FT-SBT-3IA	12,800	8,900		8,150	
111	LTE-3FB-45FT-SKT-3IA	13,716	9,350		6,050	
112	LTE-3FB-45FT-FBT-3IA	13,716	9,350		7,370	
113	LTE-3FB-45FT-SBT-3IA	13,716	9,350		8,540	
*A-Air, M-Mechanical, 1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt. 16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018. R1, R2 & R3 - Trailer Rear Axles						
** END OF DOCUMENT **						

AUTHORISED SIGNATORY		
JAYWANT HARDIKAR HEAD-CMVR	SAURABH DALELA DIRECTOR	Page 8 of 8