

ANNEXURE - I

Sr. No.	Trailer Nomenclature	Overall Length (mm)	Wheel-base (mm)	Suspension Type* & GCW (kg)	Unladen weight of trailer (kg)	Axle Spacing (m)
1	KSI-3FB-3A-26FT-FBT	8,025	4,630	MMM - 45,500 MMM - 55,000	6,200	R1 to R3 < 3m
2	KSI-3FB-3A-26FT-SBT	8,025	4,860		6,800	
3	KSI-3FB-3A-26FT-SKT	8,025	4,860		5,850	
4	KSI-3FB-3A-28FT-FBT	8,640	5,420		6,350	
5	KSI-3FB-3A-28FT-SBT	8,640	5,420		7,050	
6	KSI-3FB-3A-30FT-FBT	9,250	6,140		6,550	
7	KSI-3FB-3A-30FT-SBT	9,250	6,140		7,300	
8	KSI-3FB-3A-32FT-FBT	9,850	6,550		6,700	
9	KSI-3FB-3A-32FT-SBT	9,850	6,550		7,550	
10	KSI-3FB-3A-34FT-FBT	10,470	7,120		6,900	
11	KSI-3FB-3A-34FT-SBT	10,470	7,120		7,800	
12	KSI-3FB-3A-36FT-FBT	11,080	7,610		7,050	
13	KSI-3FB-3A-36FT-SBT	11,080	7,610		8,000	
14	KSI-3FB-3A-38FT-FBT	11,600	8,020		7,200	
15	KSI-3FB-3A-38FT-SBT	11,600	8,020		8,200	
16	KSI-3FB-3A-40FT-FBT	12,300	8,400		7,400	
17	KSI-3FB-3A-40FT-SBT	12,300	8,400		8,500	

*A-Air, M-Mechanical, 1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt.16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018.
(R1, R2 & R3 - Trailer Rear Axles)

AUTHORISED SIGNATORY		
JAYWANT HARDIKAR HEAD-CMVR	SAURABH DALELA DIRECTOR	Page 2 of 5