

ANNEXURE - I

Sr. No.	Trailer Nomenclature	Overall Length (mm)	Wheel-base (mm)	Suspension Type* & GCW (kg)	Unladen weight of trailer (kg)	Axle Spacing (m)
1	BGR-3TIP-30CUM-2+1A	8,545	5,320	MMM - 51,000 AMM - 52,000 AAA - 54,000	8,450	R1 to R3 > 3m & R2 to R3 < 1.8m
2	BGR-3TIP-32CUM TIPPER-2+1A	8,545	5,320		8,550	
3	BGR-3TIP-34CUM TIPPER-2+1A	8,875	6,110		8,930	
4	BGR-3TIP-28CUM-TIPPER-3A-55T	8,310	5,198	MMM - 55,000	8,350	R1 to R3 < 3m
5	BGR-3TIP-32CUM-TIPPER-3A-55T	8,610	5,420		8,500	
6	BGR-3TIP-34CUM-TIPPER-3A-55T	8,610	5,480		8,550	
7	BGR-3TIP-28CUM TIPPER - 3IA	8,610	5,200	MMM - 53,000 AMM - 54,000 AAA - 55,000	8,500	R1 to R3 > 3m
8	BGR-3TIP-30CUM TIPPER - 3IA	8,610	5,298		8,550	
9	BGR-3TIP-32CUM TIPPER - 3IA	8,915	5,803		9,400	
10	BGR-3TIP-34CUM TIPPER - 3IA	8,910	5,285		9,600	

\*A-Air,M-Mechanical,1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt.16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018.

R1, R2 & R3 - Trailer Rear Axles

**\*\* END OF DOCUMENT \*\***

AUTHORISED SIGNATORY		
JAYWANT HARDIKAR HEAD-CMVR		SAURABH DALELA DIRECTOR