TAC/Reference No. C T 0 N U 0 1 5

٢

ANNEXURE-I

Air Intake system	Air Filter Make		Chongqing Quanyun Machinery Manufacturing Co.Ltd./Chongqing Jinshi Air Filter Co. Ltd.				
	Type of Air Filter		Dry Foam Type				
	Fan Dimention, mm		200				
Ventilation Fan Details	Speed, rpm		3000				
	kW		0.08				
	Make			Sarover			
	External Diameter, mm		22				
Silencer Details	Length, mm			248			
	Height Above Canopy, mm			NA			
	Max. Back Pressure, kPa		0.68				
Mounting Arrangement				AVM PADS Rubber			
	Acoustic Material certificate						
Acoustic Enclosure Details	reference no.			NVH/3100007077/2020-21/1184 Dt. 30th June 2020			
	Outer Dimensions, mm			870(L)x475(B)x705(H)			
		hickness, mm	1.50				
	Insulation Material Type			PU Foam			
	Insulation Thickness, mm			15			
Density of Insulation, kg/m3			180 Kg/m ³				
Observed Noise Level at 75% load, LWA				82.68 dB(A)			
Above mentioned PG Procedure for complia	set mo ance wit	dels complies with the pr h Noise Limits for Petrol	escribe Gener	ed noise limit of 86dB(A rator Sets (up to 1000 k	() at 1 n VA)"	for Petrol Generator set at 1 m is 86 c neter from enclosure surface as per Pa	art I of "System
This cerificate is valid Production verificatior	•	Ist August, 2025. After th	nis date	e the validity of this cert	ificate s	shall be extended by the Certificate of	Conformity of
Place of Issue		Manesar		Test Report No. CT0NU0014 Dtd. 16.01.202		025	
ANJANA KUMARI IKSHIT SHRIVASTAVA Sr. Engineer Manager					SAURABH DALELA Director	Page 2 of 2	