

ANNEXURE - I

Sr. No.	Trailer Nomenclature	Overall Length (mm)	Wheel-base (mm)	Suspension Type* & GCW (kg)	Unladen weight of trailer (kg)	Axle Spacing (m)
1	VANDANA-30CUM-3A-TIP	8,641	5,516	MMM - 45,500 AAA - 45,500 MMM - 55,000 AAA - 55,000	9,350	R1 to R3 < 3m
2	VANDANA-32CUM-3A-TIP	9,200	5,987		9,560	
3	VANDANA-34CUM-3A-TIP	9,200	5,987		9,650	
4	VANDANA-36CUM-3A-TIP	9,825	6,370		9,900	
5	VANDANA-20CUM-3A-TIP	8,950	5,516		8,850	
6	VANDANA-22CUM-3A-TIP	8,950	5,516		8,950	
7	VANDANA-24CUM-3A-TIP	8,950	5,516		9,050	
8	VANDANA-26CUM-3A-TIP	8,950	5,516		9,150	
9	VANDANA-28CUM-3A-TIP	8,950	5,516		9,250	
10	VANDANA-30CUM-3A-TIP-A	8,950	5,516		9,350	

*A-Air, M-Mechanical, 1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt.16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018.

R1, R2 & R3 - Trailer Rear Axles

****END OF DOCUMENT****

AUTHORISED SIGNATORY			
JAYWANT HARDIKAR HEAD-CMVR		SAURABH DALELA DIRECTOR	Page 2 of 2