

ANNEXURE - I

Sr. No.	Trailer Nomenclature (Additional Variant)	Overall Length (mm)	Wheel-base (mm)	Suspension Type* & GCW (kg)	Unladen weight of trailer (kg)	Axle Spacing (m)
6	VANDANA-20CUM-3IA-TIP	8,950	5,516	MMM - 53,000 AMM - 54,000 AAA - 55,000	8,850	R1 to R3 > 3m
7	VANDANA-22CUM-3IA-TIP	8,950	5,516		8,950	
8	VANDANA-24CUM-3IA-TIP	8,950	5,516		9,050	
9	VANDANA-26CUM-3IA-TIP	8,950	5,516		9,150	
10	VANDANA-28CUM-3IA-TIP	8,950	5,516		9,250	
11	VANDANA-30CUM-3IA-TIP	8,950	5,516		9,350	
<p>*A-Air,M-Mechanical,1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt.16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018. R1, R2 & R3 - Trailer Rear Axles</p>						
END OF DOCUMENT						

AUTHORISED SIGNATORY			
JAYWANT HARDIKAR HEAD-CMVR		SAURABH DALELA DIRECTOR	Page 2 of 2