

## ANNEXURE - I

| Sr. No. | Trailer Nomenclature | Overall Length (mm) | Wheel-base (mm) | Suspension Type* & GCW (kg)                              | Unladen weight of trailer (kg) | Axle Spacing (m)                |
|---------|----------------------|---------------------|-----------------|----------------------------------------------------------|--------------------------------|---------------------------------|
| 1       | SAW-3TIP-20CUM-3A    | 8,230               | 5,130           | (1) MMM - 45,500<br>(2) MMM - 55,000                     | 8,310                          | R1 to R3 < 3m                   |
| 2       | SAW-3TIP-22CUM-3A    | 8,230               | 5,130           |                                                          | 8,520                          |                                 |
| 3       | SAW-3TIP-24CUM-3A    | 8,315               | 5,220           |                                                          | 8,715                          |                                 |
| 4       | SAW-3TIP-26CUM-3A    | 8,315               | 5,220           |                                                          | 8,960                          |                                 |
| 5       | SAW-3TIP-28CUM-3A    | 8,620               | 5,460           |                                                          | 9,040                          |                                 |
| 6       | SAW-3TIP-30CUM-3A    | 8,620               | 5,460           |                                                          | 9,250                          |                                 |
| 7       | SAW-3TIP-32CUM-3A    | 8,620               | 5,460           |                                                          | 9,460                          |                                 |
| 8       | SAW-3TIP-34CUM-3A    | 8,620               | 5,460           |                                                          | 9,650                          |                                 |
| 9       | SAW-3TIP-36CUM-3A    | 8,620               | 5,460           |                                                          | 9,810                          |                                 |
| 10      | SAW-3TIP-38CUM-3A    | 8,620               | 5,460           |                                                          | 10,120                         |                                 |
| 11      | SAW-3TIP-40CUM-3A    | 8,830               | 5,460           |                                                          | 10,320                         |                                 |
| 12      | SAW-3TIP-20CUM-2+1A  | 8,230               | 5,630           | (1) MMM - 51,000<br>(2) AMM - 52,000<br>(3) AAA - 54,000 | 8,510                          | R1 to R3 > 3m & R2 to R3 < 1.8m |
| 13      | SAW-3TIP-22CUM-2+1A  | 8,230               | 5,630           |                                                          | 8,720                          |                                 |
| 14      | SAW-3TIP-24CUM-2+1A  | 8,315               | 5,720           |                                                          | 8,915                          |                                 |
| 15      | SAW-3TIP-26CUM-2+1A  | 8,315               | 5,720           |                                                          | 9,160                          |                                 |
| 16      | SAW-3TIP-28CUM-2+1A  | 8,620               | 5,955           |                                                          | 9,240                          |                                 |
| 17      | SAW-3TIP-30CUM-2+1A  | 8,620               | 5,955           |                                                          | 9,450                          |                                 |
| 18      | SAW-3TIP-32CUM-2+1A  | 8,620               | 5,955           |                                                          | 9,660                          |                                 |

\*A-Air, M-Mechanical, 1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt. 16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018.

**R1, R2 & R3 - Trailer Rear Axles****AUTHORISED SIGNATORY**

|                               |  |                            |             |
|-------------------------------|--|----------------------------|-------------|
|                               |  |                            |             |
| JAYWANT HARDIKAR<br>HEAD-CMVR |  | SAURABH DALELA<br>DIRECTOR | Page 2 of 3 |

## ANNEXURE - I

| Sr. No. | Trailer Nomenclature | Overall Length (mm) | Wheel-base (mm) | Suspension Type* & GCW (kg)                              | Unladen weight of trailer (kg) | Axle Spacing (m)                   |
|---------|----------------------|---------------------|-----------------|----------------------------------------------------------|--------------------------------|------------------------------------|
| 19      | SAW-3TIP-34CUM-2+1A  | 8,620               | 5,955           | (1) MMM - 51,000<br>(2) AMM - 52,000<br>(3) AAA - 54,000 | 9,850                          | R1 to R3 > 3m &<br>R2 to R3 < 1.8m |
| 20      | SAW-3TIP-36CUM-2+1A  | 8,620               | 5,955           |                                                          | 10,100                         |                                    |
| 21      | SAW-3TIP-38CUM-2+1A  | 8,620               | 5,955           |                                                          | 10,320                         |                                    |
| 22      | SAW-3TIP-40CUM-2+1A  | 8,830               | 5,955           |                                                          | 10,520                         |                                    |
| 23      | SAW-3TIP-20CUM-3IA   | 8,230               | 5,130           | (1) MMM - 53,000<br>(2) AMM - 54,000<br>(3) AAA - 55,000 | 8,510                          | R1 to R3 > 3m                      |
| 24      | SAW-3TIP-22CUM-3IA   | 8,230               | 5,130           |                                                          | 8,720                          |                                    |
| 25      | SAW-3TIP-24CUM-3IA   | 8,315               | 5,220           |                                                          | 8,915                          |                                    |
| 26      | SAW-3TIP-26CUM-3IA   | 8,315               | 5,220           |                                                          | 9,160                          |                                    |
| 27      | SAW-3TIP-28CUM-3IA   | 8,620               | 5,460           |                                                          | 9,240                          |                                    |
| 28      | SAW-3TIP-30CUM-3IA   | 8,620               | 5,460           |                                                          | 9,450                          |                                    |
| 29      | SAW-3TIP-32CUM-3IA   | 8,620               | 5,460           |                                                          | 9,660                          |                                    |
| 30      | SAW-3TIP-34CUM-3IA   | 8,620               | 5,460           |                                                          | 9,850                          |                                    |
| 31      | SAW-3TIP-36CUM-3IA   | 8,620               | 5,460           |                                                          | 10,100                         |                                    |
| 32      | SAW-3TIP-38CUM-3IA   | 8,620               | 5,460           |                                                          | 10,320                         |                                    |
| 33      | SAW-3TIP-40CUM-3IA   | 8,830               | 5,460           |                                                          | 10,520                         |                                    |

\*A-Air, M-Mechanical, 1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt. 16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018.

**R1, R2 & R3 - Trailer Rear Axles**

**\*\* END OF DOCUMENT \*\***

| AUTHORISED SIGNATORY          |  |                            |                |
|-------------------------------|--|----------------------------|----------------|
|                               |  |                            |                |
| JAYWANT HARDIKAR<br>HEAD-CMVR |  | SAURABH DALELA<br>DIRECTOR | Page 3 of<br>3 |