

ANNEXURE - I

Sr. No.	Trailer Nomenclature	Overall Length (mm)	Wheel-base (mm)	Suspension Type & GCW (kg)	Unladen weight of trailer (kg)	Axle Spacing (m)
1	JWL-SA-22CUM SMT	8,866	6,594	MMM - 51,000 AMM - 52,000 AAA - 54,000	7,500	R1 to R3 > 3m & R2 to R3 < 1.8 m
2	JWL-SA-24CUM SMT	8,866	6,594		7,600	
3	JWL-SA-26CUM SMT	8,866	6,594		7,700	
4	JWL-SA-28CUM SMT	8,887	6,577		7,800	
5	JWL-SA-30CUM SMT	9,115	6,825		7,900	
6	JWL-SA-32CUM SMT	9,115	6,825		8,000	
7	JWL-SA-34CUM SMT	10,540	8,030		8,100	
8	JWL-SA-36CUM SMT	10,540	8,030		8,200	
9	JWL-SA-38CUM SMT	10,950	8,200		8,300	
10	JWL-SA-38CUM SMT	10,950	8,200		8,400	
11	JWL-SA-42CUM SMT	10,950	8,200		8,450	
12	JWL-SA-45CUM SMT	11,500	8,650		8,600	
13	JWL-IA-22CUM SMT	8,868	5,688	MMM - 53,000 AMM - 54,000 AAA - 55,000	7,500	R1 to R3 > 3m
14	JWL-IA-24CUM SMT	8,865	5,685		7,600	
15	JWL-IA-26CUM SMT	8,864	5,684		7,700	
16	JWL-IA-28CUM SMT	8,867	5,687		7,800	
17	JWL-IA-30CUM SMT	9,116	5,936		7,900	
18	JWL-IA-32CUM SMT	9,116	5,936		8,000	

*A-Air,M-Mechanical,1 tonne extra load is permitted for each axle fitted with pneumatic suspension as per S.O. 3467(E) dt.16th July, 2018, with S.O. 3881(E) dt. 06th August, 2018.

R1, R2 & R3 - Trailer Rear Axles**AUTHORISED SIGNATORY**

JAYWANT HARDIKAR HEAD-CMVR		SAURABH DALELA DIRECTOR	Page 2 of 3