

ANNEXURE - I

Rule No.	Sub Rule(s)	Compliance Verified For		Standard	
93	(1)(A), (1)(B) & 2	Motor vehicle width, length and height		-	
94	(1), (2) & (3)	Condition of tyres		-	
95	(1), (2), (3), (4), (5) & (6) (Tubeless)	Size & ply rating of tyres		IS 15627:2005 & AIS-050:2004	
		Front	90/90-12 54J, (For 1, & 2)		1. TVS 2. CEAT
		Rear	90/90-12, 64B (For 3)		3. JK Tyre
96	(1), (2), (3),(4)(ib), (7)(c) & (8)	Brakes		IS 14664:2010	
102	(1), (2) & (3)	Signaling devices, direction indicators and stop lights		-	
103	(1)	Position of the indicator		-	
104	(1) & (4)	Fitment of reflectors		AIS-057 (Rev. 1): 2010	
105	(1)(bb), (2)(i) & (4)	Lamps		-	
106	(1)	Deflection of lights		-	
108	(1)	Use of red or white lights		-	
111	-	Prohibition of spotlights etc.		-	
117	(1) & (2)	Speedometer		IS 11827:2008	
119	(1) & (2)	Horns	Installation (Below 7kW)		IS 15796:2008
			Limit :	83 dB(A) to 112 dB(A)	
			Observed :	97.5 dB(A)	
			Performance		IS 1884:1993
120	(2)	Pass by Noise	Limit :	75 dB(A)	IS 3028:1998
			Observed :	58 dB(A)	
122	(1) & (2)	Embossment of chassis number & motor number & month of manufacture (Ref: Table 11 of the Technical Specifications)		AIS-065:2005	
123	(1)	Safety devices in motor cycle		Pillion Handhold	IS 14495:1998
	(2)			Footrests	AIS 148:2018
	(4)			Stand	AIS 146:2018
	(5)			External Projection	AIS 147:2018
124	Refer Annexure-IA & IB	Safety standards of components as applicable		-	
125	(2)(a)	Rear View Mirror	Specifications		AIS-001 (Part 2) (Rev.1):2011
			Installation		AIS-002 (Part 2) (Rev.1):2011

ICAT Ref No.	2024-0607; IOCS Ref: 178351
Power Test Report No.	CT0PT 0709 Dt. 21.10.2024
Noise Report No.	CT0VT 1617 Dt. 10.10.2024
Horn Inst. Report No.	CT0VT 1616 Dt. 10.10.2024

AUTHORISED SIGNATORY		
JAYWANT HARDIKAR HEAD-CMVR	SAURABH DALELA DIRECTOR	Page 2 of 4