

ANNEXURE - I

Rule No.	Sub Rule(s)	Compliance Verified For		Standard	
93	(1)(A), (1)(B) & (2)	Motor Vehicle width, length & height		-	
94	(1), (2) & (3)	Condition of tyres		-	
95	(1), (2), (3), (4), (5) & (6) (Tubeless)	Size & ply rating of tyres		IS 15627:2005 & AIS-050:2004	
		Front	100/90-19 M/C 57H		MRF tyre
		Rear	150/70-17 M/C 69 H 130/70-18M/C 63H		
96	(1), (2), (3), (4)(ib), (4A), (7)(c) & (8)	Brakes with ABS		IS 14664:2010	
102	(1), (2) & (3)	Signaling devices, direction indicators and stop lights		-	
103	(1)	Position of the indicator		-	
104	(1) & (4)	Fitment of reflectors		AIS-057 (Rev. 1): 2010	
105	(1)(bb), (2)(i) & (4)	Lamps		-	
106	(1)	Deflection of lights		-	
108	(1)	Use of red or white lights		-	
111	-	Prohibition of spotlights etc.		-	
114	(1) & (2)	Exhaust gases and exhaust pipes		-	
115	(1), (2)(i) & (19)(i)	Emission of smoke, vapour, etc. from motor vehicle		AIS-137	
117	(1) & (2)	Speedometer		IS 11827:2008	
119	(1) & (2)	Horns	Installation (Above 7kW)		IS 15796:2008
			Limit :	87 dB(A) to 112 dB(A)	
			Observed :	102.2 & 101.3 dB(A)	
			Performance		IS 1884:1993
120	(1)	Silencers		-	
	(2)	Pass by Noise	Limit :	80 dB(A) (80 < cc ≤ 175)	IS 3028:1998
			Observed :	77 & 76.9 dB(A)	
122	(1) & (2)	Embossment of chassis number & engine number & month of manufacture (Ref: Table 11 of the Technical Specifications)		AIS-065:2005	
123	(1)	Pillion Hand Hold		IS 14495:1998	
	(2)	Footrest		AIS 148:2018	
	(4)	Stand		AIS 146:2018	
	(5)	External projection		AIS 147:2018	
124	Refer Annexure-IA & IB	Safety standards of components as applicable		-	
125	(2)(a)	Rear View Mirror	Specifications		AIS-001 (Part 2) (Rev.1):2011
			Installation		AIS-002 (Part 2) (Rev.1):2011

ICAT Ref No.	2024-1431; IOCS Ref:- 181586
Emission Report No.	CT0PU0172 dt. 03.02.2025
Noise Report No.	CT0VU 0242 & CT0VU 0245 dt. 03.02.2025
Horn Inst. Report No.	CT0VS 0232 dt. 15.02.2023 & CT0VS 0233 dt. 15.02.2023
FTP Report No.	CT0EU 0034 dt. 22.01.2025

AUTHORISED SIGNATORY			
JAYWANT HARDIKAR HEAD-CMVR		SAURABH DALELA DIRECTOR	
			Page 2 of 4