

ANNEXURE - I

Rule No.	Sub Rule(s)	Compliance Verified For		Standard	
93	(1)(A), (1)(B), (2)	Motor vehicle width, length and height		-	
94	(1), (2), (3)	Condition of tyres		-	
95	(1), (2),(3), (4), (5) & (6) (Tube Type)	Size & ply rating of tyres		IS 15627:2005 & AIS-050-2004	
		Front/ Rear	3.75-12, 66E 4PR		MRF
			3.75-12, 60J 4PR		TVS
96	(1), (2), (3), (4)(i), (7)(b)	Brakes		IS 14664:1999	
99	-	Forward and backward motion		-	
100	(1), (2), (3)	Safety glass		NA	
101	(1)	Windscreen Wiper		NA	
102	(1), (2)	Signaling devices, direction indicators and stop lights		-	
103	(1), (2)	Position of the indicator		-	
104	(1)(v),(4)	Fitment of reflectors & reflective tapes		AIS-057(Rev.1):2010 & AIS090-2005	
105	(1)(b), (3), (4), (5), (7)	Lamps		-	
106	(1)	Deflection of lights		-	
108	(1)	Use of red or white lights		-	
109	-	Parking lights		-	
110	-	Lamps for three wheelers		-	
111	-	Prohibition of spotlights etc.		-	
119	(1) & (2)	Horns	Installation		IS 15796:2008
			Limit :	83 dB(A) to 112 dB(A)	
			Observed :	98.3 dB(A)	
			Performance		IS 1884:1993
122	(1) & (2)	Embossment of chassis number & motor number & month of manufacture (Ref: Table 11 of the Technical Specifications)		AIS-065-2005	
124	-	Safety standards of components as applicable		Refer ANNEXURE - IA & IB	
125	(2)(a)	Rear View Mirror	Specifications		AIS-001 (Part-2)Rev.1:2011
			Installation		AIS-002 (Part-2)Rev.1:2011

ICAT Ref No.	2024-0795 (178375)
Power Test Report No.	CT0PT 0403 dt. 17.05.2024
Horn Inst. Report No.	CT0VT 0486 dt. 22.03.2024

AUTHORISED SIGNATORY		
JAYWANT HARDIKAR HEAD-CMVR	SAURABH DALELA DIRECTOR	Page 2 of 3