

ANNEXURE - I

Rule No.	Sub Rule(s)	Compliance Verified For		Standard
93	(1)(A), (1)(B) & (2)	Motor vehicle width, length and height		-
94	(1), (2) & (3)	Condition of tyres		-
95	(1), (2), (3), (4), (5) & (6) (Tubeless)	Size & ply rating of tyres		IS 15627:2005 & AIS-050:2004
		Front/ Rear	90/90-12-54J	
			90/90-12-54L	
96	(1), (2), (3), (4)(ib), (4A), (7)(c) & (8)	Brakes with ABS		IS 14664:2010
102	(1), (2) & (3)	Signaling devices, direction indicators and stop lights		-
103	(1)	Position of the indicator		-
104	(1) & (4)	Fitment of reflectors		AIS-057 (Rev. 1): 2010
105	(1)(bb), (2) & (4)	Lamps		-
106	(1)	Deflection of lights		-
108	(1)	Use of red or white lights		-
111	-	Prohibition of spotlights etc.		-
117	(1) & (2)	Speedometer		IS 11827:2008
119	(1) & (2)	Horns	Installation (Below 7kW)	IS 15796:2008
			Limit : 83 dB(A) to 112 dB(A)	
			Observed : 89.1 dB(A)	
			Performance	IS 1884:1993
120	(2)	Pass by Noise	Limit : 75 dB(A)	IS 3028:1998
			Observed : 62 dB(A)	
122	(1) & (2)	Embossment of chassis number & motor number & month of manufacture (Ref: Table 11 of the Technical Specifications)		AIS-065:2005
123	(1)	Safety devices in motor cycle	Pillion Handhold	IS 14495:1998
	(2)		Footrests	AIS 148:2018
	(4)		Stand	AIS 146:2018
	(5)		External Projection	AIS 147:2018
124	Refer Annexure-IA & IB	Safety standards of components as applicable		-
125	(2)(a)	Rear View	Specifications	AIS-001 (Part 2) (Rev.1):2011
		Mirror	Installation	AIS-002 (Part 2) (Rev.1):2011

ICAT Ref No.	2024-0863 (IOCS Ref: 179436)
Power Test Report No.	CT0ES 0174 dt. 30.03.2023
Noise Report No.	CT0VU 0012 dt. 02.01.2025
Horn Inst. Report No.	CT0VU 0011 dt. 02.01.2025

AUTHORISED SIGNATORY			Page 2 of 4
JAYWANT HARDIKAR HEAD-CMVR		SAURABH DALELA DIRECTOR	